

Console

Mic/Line In	1 ~ 30	~ Blank Ch ~
	31	From Monitor Console Backup Mix(L)
	32	From Monitor Console Backup Mix(R)
Line Out	1 ~ 16	~ Blank Ch ~
	17	Hall Send (L)
	18	Hall Send (R)
	19	Rec Splitter (L)
	20	Rec Splitter (R)
	21	In Fill (L)
	22	In Fill (R)
	23 ~ 24	~ Blank Ch ~
	25 (C)	~ Blank Ch ~
	26 (R)	Main (R)
	27 (L)	Main (L)
Moni A	Left	~ Blank Ch ~
	Center	~ Blank Ch ~
	Right	~ Blank Ch ~
Moni B	Left	~ Blank Ch ~
	Right	~ Blank Ch ~

AES In	1/2	~ Blank Ch ~
	3/4	~ Blank Ch ~
AES Out	1/2	~ Blank Ch ~
	3/4	~ Blank Ch ~
SPDIF In		~ Blank Ch ~
SPDIF Out		~ Blank Ch ~



As shown in the photo, the first number on Vi1 is marked R, so the standard patch is also set accordingly.

【Vi1 Specification】

Firmware version 4.9.2.306

There is a link on the O-EAST homepage for the EAST default data , so Please download it from there.

(It will be 1 ZIP file including Vi1)

[Regarding the mix of main console(S6L) and sub console(Vi1)]

It is mixed by passive device and sent to a speaker processor etc.